

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010



Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: RENOLIT ALKORPLUS CONTACT ADHESIVE

81701010

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Adhesive. For professional users/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

RENOLIT IBERICA SA Ctra. del Montnegre, s/n

08470 Sant Celoni - Barcelona - España Phone: +34 938484000 - Fax: +34 938675936

renolit.iberica@renolit.com http://www.renolit.com/

1.4 Emergency telephone number: +44 1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Flam. Liq. 2: Flammable liquids, Category 2, H225

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P312: Call a POISON CENTER/doctor if you feel unwell.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

UFI: 1910-G0MW-200J-R8D8

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 1/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010





Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration		
CAS: EC:	64742-49-0 927-510-4	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics □¹□ Self-classified					
Index:	Non-applicable : 01-2119475515-33- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	(1) (a) (b) (b)	10 - <30 %		
CAS: EC:	110-82-7 203-806-2	cyclohexane □¹ □		ATP CLP00			
Index:	601-017-00-1 : 01-2119463273-41- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	(1) (a) (b) (b)	15 - <25 %		
CAS: EC:	64742-49-0 931-254-9	Hydrocarbons, C6, iso	oalkanes, <5% n-hexane □¹□	Self-classified			
Index:	Non-applicable : 01-2119484651-34- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	(1) (a) (b) (b)	5 - <15 %		
CAS: EC:	Non-applicable	Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics□¹□ Self-classified					
Index:	920-750-0 Non-applicable : 01-2119473851-33- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	(!) (i) (i) (i)	<15 %		
CAS:	78-93-3 201-159-0	Butanone□¹□		ATP CLP00			
EC: Index: REACH	606-002-00-3 : 01-2119457290-43- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	(!)	<10 %		
CAS: EC:	110-54-3 203-777-6	n-hexane□¹□		ATP CLP00			
Index:	601-037-00-0 : 01-2119480412-44- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361f; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	(1) (2) (\$\frac{1}{4}\)	<0,75 %		

[□]¹□ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
n-hexane CAS: 110-54-3 EC: 203-777-6	% (w/w) >=5: STOT RE 2 - H373

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010



Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO□).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 3/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010



Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits			
cyclohexane	IOELV (8h)	200 ppm	700 mg/m ³	
CAS: 110-82-7 EC: 203-806-2	IOELV (STEL)			
Butanone	IOELV (8h)	200 ppm	600 mg/m ³	
CAS: 78-93-3 EC: 201-159-0	IOELV (STEL)	300 ppm	900 mg/m ³	
n-hexane	IOELV (8h)	20 ppm	72 mg/m³	
CAS: 110-54-3 EC: 203-777-6	IOELV (STEL)			

DNEL (Workers):



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	300 mg/kg	Non-applicable
EC: 927-510-4	Inhalation	Non-applicable	Non-applicable	2085 mg/m ³	Non-applicable
cyclohexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	2016 mg/kg	Non-applicable
EC: 203-806-2	Inhalation	1400 mg/m³	1400 mg/m³	700 mg/m³	700 mg/m³
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	13964 mg/kg	Non-applicable
EC: 931-254-9	Inhalation	Non-applicable	Non-applicable	5306 mg/m³	Non-applicable
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	773 mg/kg	Non-applicable
EC: 920-750-0	Inhalation	Non-applicable	Non-applicable	2035 mg/m ³	Non-applicable
Butanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	600 mg/m ³	Non-applicable
n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 110-54-3	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
EC: 203-777-6	Inhalation	Non-applicable	Non-applicable	75 mg/m³	Non-applicable

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Oral	Non-applicable	Non-applicable	149 mg/kg	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	149 mg/kg	Non-applicable
EC: 927-510-4	Inhalation	Non-applicable	Non-applicable	447 mg/m³	Non-applicable
cyclohexane	Oral	Non-applicable	Non-applicable	59,4 mg/kg	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	1186 mg/kg	Non-applicable
EC: 203-806-2	Inhalation	412 mg/m³	412 mg/m³	206 mg/m³	206 mg/m ³
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Oral	Non-applicable	Non-applicable	1301 mg/kg	Non-applicable
CAS: 64742-49-0	Dermal	Non-applicable	Non-applicable	1377 mg/kg	Non-applicable
EC: 931-254-9	Inhalation	Non-applicable	Non-applicable	1131 mg/m³	Non-applicable
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics	Oral	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	699 mg/kg	Non-applicable
EC: 920-750-0	Inhalation	Non-applicable	Non-applicable	608 mg/m³	Non-applicable
Butanone	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
CAS: 78-93-3	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
EC: 201-159-0	Inhalation	Non-applicable	Non-applicable	106 mg/m³	Non-applicable
n-hexane	Oral	Non-applicable	Non-applicable	4 mg/kg	Non-applicable
CAS: 110-54-3	Dermal	Non-applicable	Non-applicable	5,3 mg/kg	Non-applicable
EC: 203-777-6	Inhalation	Non-applicable	Non-applicable	16 mg/m³	Non-applicable

PNEC:

Identification				
cyclohexane	STP	3,24 mg/L	Fresh water	0,207 mg/L
CAS: 110-82-7	Soil	3,38 mg/kg	Marine water	0,207 mg/L
EC: 203-806-2	Intermittent	0,207 mg/L	Sediment (Fresh water)	16,68 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,68 mg/kg

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 5/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010



Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Butanone	STP	709 mg/L	Fresh water	55,8 mg/L
CAS: 78-93-3	Soil	22,5 mg/kg	Marine water	55,8 mg/L
EC: 201-159-0	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	7	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Picto	ogram	PPE	Labelling	CEN Standard	Remarks
Mandator	ry complete protection	Antistatic and fireproof protective clothing	CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
	atory foot dection	Safety footwear with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.


F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

RENOLIT Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation







RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 61 % weight
V.O.C. density at 25 °C: Non-applicable

Average carbon number: 6,42

Average molecular weight: 91,96 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

Appearance:

Colour:

Yellow

Odour:

Hydrocarbon

Odour threshold:

Non-applicable *

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 25 °C:

Vapour pressure at 50 °C:

Non-applicable *

Non-applicable *

Evaporation rate at 25 °C:

Non-applicable *

Product description:

Density at 25 °C: Non-applicable * Relative density at 25 °C: 0,75 - 0,85 Dynamic viscosity at 25 °C: 600 - 1200 cP Kinematic viscosity at 25 °C: Non-applicable * Kinematic viscosity at 40 °C: Non-applicable * Concentration: Non-applicable * pH: Non-applicable * Vapour density at 25 °C: Non-applicable * Partition coefficient n-octanol/water 25 °C: Non-applicable * Solubility in water at 25 °C: Non-applicable * Solubility properties: Insoluble in water Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: -26 °C

Flammability (solid, gas):

Autoignition temperature:

Non-applicable *
>200 °C

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 7/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010



Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Lower flammability limit: Not available
Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Non-applicable *

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 25 °C:

Non-applicable *

Refraction index:

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO \square), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 8/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010



Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (3); Hydrocarbons, C6, isoalkanes, <5% n-hexane (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification		Acute toxicity		Genus
Butanone		LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3		LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0		LC50 inhalation	23,5 mg/L (4 h)	Rat
cyclohexane		LD50 oral	5100 mg/kg	Rat
CAS: 110-82-7		LD50 dermal	Non-applicable	
EC: 203-806-2		LC50 inhalation	Non-applicable	
n-hexane		LD50 oral	>5000 mg/kg	Mouse
CAS: 110-54-3		LD50 dermal	>5000 mg/kg	Rabbit
EC: 203-777-6		LC50 inhalation	Non-applicable	

11.2 Information on other hazards:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation







RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LC50	>1 - 10 (96 h)		Fish
CAS: 64742-49-0	EC50	>1 - 10 (48 h)		Crustacean
EC: 927-510-4	EC50	>1 - 10 (72 h)		Algae
cyclohexane	LC50	>0.1 - 1 (96 h)		Fish
CAS: 110-82-7	EC50	>0.1 - 1 (48 h)		Crustacean
EC: 203-806-2	EC50	>0.1 - 1 (72 h)		Algae
Hydrocarbons, C6, isoalkanes, <5% n-hexane	LC50	Non-applicable		
CAS: 64742-49-0	EC50	3,87 mg/L (48 h)	Daphnia magna	Crustacean
EC: 931-254-9	EC50	55 mg/L (72 h)	Scenedesmus subspicatus	Algae
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics	LC50	>1 - 10 (96 h)		Fish
CAS: Non-applicable	EC50	>1 - 10 (48 h)		Crustacean
EC: 920-750-0	EC50	>1 - 10 (72 h)		Algae
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-159-0	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
n-hexane	LC50	4 mg/L (96 h)	Carassius auratus	Fish
CAS: 110-54-3	EC50	Non-applicable		
EC: 203-777-6	EC50	Non-applicable		

Chronic toxicity:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 10/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	NOEC	Non-applicable		
CAS: 64742-49-0 EC: 927-510-4	NOEC	0,17 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Deg	radability	Biodeg	gradability
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 64742-49-0	COD	Non-applicable	Period	14 days
EC: 927-510-4	BOD5/COD	Non-applicable	% Biodegradable	95 %
cyclohexane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 110-82-7	COD	Non-applicable	Period	28 days
EC: 203-806-2	BOD5/COD	Non-applicable	% Biodegradable	0 %
Hydrocarbons, C6, isoalkanes, <5% n-hexane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64742-49-0	COD	Non-applicable	Period	28 days
EC: 931-254-9	BOD5/COD	Non-applicable	% Biodegradable	98 %
Hydrocarbons, C7-C9,n-alkanes, iso-alkanes, cyclics	BOD5	Non-applicable	Concentration	Non-applicable
CAS: Non-applicable	COD	Non-applicable	Period	28 days
EC: 920-750-0	BOD5/COD	Non-applicable	% Biodegradable	98 %
Butanone	BOD5	2,03 g O2/g	Concentration	Non-applicable
CAS: 78-93-3	COD	2,31 g O2/g	Period	20 days
EC: 201-159-0	BOD5/COD	0,88	% Biodegradable	89 %
n-hexane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 110-54-3	COD	Non-applicable	Period	14 days
EC: 203-777-6	BOD5/COD	Non-applicable	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
cyclohexane	BCF	66	
CAS: 110-82-7	Pow Log	3.44	
EC: 203-806-2	Potential	Moderate	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	BCF	501	
CAS: 64742-49-0	Pow Log	3.6	
EC: 931-254-9	Potential	High	

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 11/15





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

81701010

RENOLIT ALKORPLUS CONTACT ADHESIVE







Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification Bioaccumulation potential		nulation potential	
Butanone	BCF		3
.		/ Log	0.29
		ential	Low
n-hexane	BCF	=	542
		/ Log	3.9
		ential	High

12.4 Mobility in soil:

Identification	Absorption/desorption		Volat	ility
cyclohexane	Koc	Non-applicable	Henry	Non-applicable
CAS: 110-82-7	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-806-2	Surface tension	2,465E-2 N/m (25 °C)	Moist soil	Non-applicable
Butanone	Koc	30	Henry	5,77 Pa·m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
EC: 201-159-0	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
n-hexane	Koc	150	Henry	185425 Pa·m³/mol
CAS: 110-54-3	Conclusion	High	Dry soil	Yes
EC: 203-777-6	Surface tension	1,798E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 12/15



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

RENOLIT ALKORPLUS **CONTACT ADHESIVE** 81701010





Version: 3 (Replaced 2) Date of compilation: 28/10/2020 Revised: 17/09/2022

SECTION 14: TRANSPORT INFORMATION (continued)



UN1133 14.1 **UN number or ID number:** UN proper shipping name: **ADHESIVES** 14.2

14.3 Transport hazard class(es): Labels: 3 14.4 Packing group: Ш 14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: Non-applicable

Tunnel restriction code: D/F

Physico-Chemical properties: see section 9


Limited quantities:

Maritime transport in bulk Non-applicable

according to IMO instruments:

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



14.6 Special precautions for user

Special regulations: Non-applicable F-E, S-D EmS Codes: Physico-Chemical properties: see section 9

Limited quantities: 5 L

Non-applicable Segregation group: Maritime transport in bulk Non-applicable according to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 **UN** number or ID number: UN1133 UN proper shipping name: **ADHESIVES** 142

Transport hazard class(es): Labels: 3 14.4 Packing group: Ш **Environmental hazards:** 14.5 Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9

Maritime transport in bulk Non-applicable

according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

- CONTINUED ON NEXT PAGE -

Revised: 17/09/2022 Date of compilation: 28/10/2020 Version: 3 (Replaced 2) Page 13/15

RENOLIT Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation







RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION (continued)

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

:

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 2: H361f - Suspected of damaging fertility.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

Abbreviations and acronyms:

- CONTINUED ON NEXT PAGE -

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2) Page 14/15

Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation







RENOLIT ALKORPLUS CONTACT ADHESIVE 81701010

Date of compilation: 28/10/2020 Revised: 17/09/2022 Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -